# KONTOUR 1200-1500 HYDRO

**Categories:** KONTOUR, Lathes

## LATHE WITH HYDRAULIC COPYING DEVICE KONTOUR 1200 HYDRO - KONTOUR 1500 HYDRO

## TECHNICAL DATA

| | KONTOUR 1200 HYDRO | KONTOUR 1500 HYDRO |
|---|---|---|
| Distance between centres | mm 1200 | mm 1500 |
| Height of centres over bed | mm 240 | mm 240 |
| Max. turning diameter | mm 460 (max. square mm 330) | mm 460 (max. square mm 330) |
| Max turning diameter with copying device | mm 200 (max. square mm 130) | mm 200 (max. square mm 130) |

| | | |
|---|---|---|
| Useful copying stroke | mm 1100 | mm 1400 |
| Chuck speed | rpm 900/1500/2100/2800 | rpm 900/1500/2100/2800 |
| Motor power | HP 3 | HP 3 |
| Feed motor power | HP 0,5 | HP 0,5 |
| Weight | kg 450 | kg 460 |

## STANDARD EQUIPMENT

- Hydraulic copying device with motorized feed
- Copying tool
- Gouge support mm 350
- Chuck entrainer ø 25 mm
- Rotating tailstock
- Service spanners

## CE EQUIPMENT

- Hydraulic copying device with motorized feed
- Copying tool
- Gouge support mm 350
- Chuck entrainer ø 25 mm
- Rotating tailstock
- Service spanners
- Self-braking motor
- Dust extraction hood ø 80 mm