MC 300

Categories: Multi-Rip Saw

MULTI-RIP SAW MC 300

TECHNICAL DATA

Min./max. cutting width	mm 10/120
Min length of pieces	mm 600
Max passage	mm 760
Min./max. blade diameter	mm 205/380
Blade hole diameter	mm 70
Spindle diameter	mm 55

Blade revolutions	rpm 4000
Max external distance between the 2 blades	mm 300
Mat width	mm 300
Feed speed	m/min 4-30
Main motor power	HP 50
Feed motor power	HP 3
Lifting pressure rollers motor power	HP 0,5
External diameter of suction hood	mm 150x2
Working table dimension	mm 760x1730
Working table height from the floor	mm 740
Weight	kg 2300

STANDARD EQUIPMENT

- Blade sleeve complete with spacer rings as follow: nr.2 mm 50 / nr.4 mm 20 / nr.4 mm 15 / nr.4 mm 10 / nr.4 mm 5 / nr.4 mm 2 / nr.4 mm 1 / nr.4 mm 0,5 / nr.4 mm 0,3
- Automatic lubrication

CE EQUIPMENT

- Blade sleeve complete with spacer rings as follow: nr.2 mm 50 / nr.4 mm 20 / nr.4 mm 15 / nr.4 mm 10 / nr.4 mm 5 / nr.4 mm 2 / nr.4 mm 1 / nr.4 mm 0,5 / nr.4 mm 0,3
- Automatic lubrication
- CE wiring