

# R 600-800-900



Categories: [Routers](#)

## ROUTERS R 600 - R 800 - R 900

### TECHNICAL DATA

|                              | <b>R 600</b>   | <b>R 800</b>   | <b>R 900</b>   |
|------------------------------|----------------|----------------|----------------|
| Chuck - column distance      | mm 600         | mm 800         | mm 900         |
| Shaft vertical stroke        | mm 80          | mm 80          | mm 80          |
| Table dimensions             | mm 800x600     | mm 800x600     | mm 800x600     |
| Vertical stroke of the table | mm 140         | mm 140         | mm 140         |
| Motor power                  | HP 2/3         | HP 3/4         | HP 3/4         |
| Speed rotation               | rpm 9000/18000 | rpm 9000/18000 | rpm 9000/18000 |
| Weight                       | kg 240         | kg 250         | kg 300         |

## **STANDARD EQUIPMENT**

- Belt drive motor
- Main switch with push button
- Nr.1 collet Ø 10mm e nr.1 collet Ø 12mm, nr.2 chuck locking wrenches e nr.5 templates Ø 6,8,10,12,14 mm (R 900)

## **CE EQUIPMENT**

- Belt drive motor
- Main switch with push button
- Emergency push-button
- Dust extraction hood
- Safety switch on the brake
- Thermal relay on motor
- Table dimension mm 1.000 x 800
- Nr.1 collet Ø 10mm e nr.1 collet Ø 12mm, nr.2 chuck locking wrenches e nr.5 templates Ø 6,8,10,12,14 mm (R 900)