T 120 - TL 120

Categories: Spindle Moulders, T 120

SPINDLE MOULDER T 120 - TL 120

TECHNICAL DATA

	T 120	TL 120
Working table dimensions	mm 920x1100	mm 920x2300
Available spindle diameters	mm 30-35-40-50	mm 30-35-40-50
Max table opening	mm 350x80	mm 350x80
Vertical stroke (spindle Ø 30-35)	mm 140	mm 140
Vertical stroke (spindle Ø 40-50)	mm180	mm180
Working table height	mm 890	mm 890
Spindle speed	rpm 2500/4200/6000/8000/10000	rpm 2500/4200/6000/8000/10000
Motor power	HP 5,5	HP 5,5
Weight	kg 590	kg 680

STANDARD EQUIPMENT

- Spindle hood
- 2 dust extraction hoods (1 x ø 80 mm, 1 x ø 120 mm)
- Manual star/delta switch

CE EQUIPMENT

- Spindle hood
- Fence with linear handling through hand-wheels and displacements displayed by decimal mechanical numerators. Scrolling on linear ball recirculation guides
- 2 dust extraction hoods (1x ø80mm,1xø120 mm)
- Profiling spindle hood
- Rounding spindle hood
- Automatic star/delta switch
- Self-braking motor
- Electrical configuration for feeder
- Spindle upstroke readout
- Readout for spindle speed
- Spindle protections CE type