TT 120 EVO - TTL 120 EVO

Categories: Spindle Moulders, T 120 EVO



TENONING SPINDLE MOULDER TT 120 EVO - TTL 120 EVO

TECHNING DATA

	TT 120 EVO	**TTL 120 EVO**
Working table dimensions	mm 745x1100	mm 920x1700
Available spindle diameters	mm 30-35-40-50	mm 30-35-40-50
Max table opening	mm 350x80	mm 350x80
Vertical stroke (spindle Ø 30-35)	mm 140	mm 140
Vertical stroke (spindle Ø 40-50)	mm180	mm180
Working table height	mm 890	mm 890
Spindle speed	da rpm 800 a 10000 con inverter	da rpm 800 a 10000 con inverter
Motor power	HP 7,5	HP 7,5
Weight	kg 750	kg 850

CE EQUIPMENT

- Profiling spindle hood with dust extraction hood ø 120 mm
- Tenoning spindle hood with dust extraction hood ø 120 mm
- Fence with linear handling through hand-wheels and displacements displayed by decimal mechanical numerators. Scrolling on linear ball recirculation guides.
- Dust extraction hood on the back ø 80 mm
- Telescopic fence with 2 stops
- Eccentric clamp
- CE protections
- Electrical configuration for feeder
- Revolver for workpiece length reference
- Adjustable frontal bar for big dimensions pieces (for TTL 120 EVO)
- Reverse rotation
- Hanging control panel
- Movements managed by 8” touch screen control panel with manual, semi-automatic and automatic function.
- The control positions the tool according to the size of the tool.
- Motor start managed by inverter
- Variable speed from 800 to 10.000 rpm managed by control panel